

W334e

Bright projection









- Bright WXGA projector 3700 ANSI lumens
- Easy connectivity HDMI, VGA, USB Power
- Clear, powerful audio 10W speaker
- Lightweight and portable

Project bright vibrant presentations effortlessly any time of day in HD. Designed for meeting rooms and classrooms, the W334e boasts amazing colour, long lamp life and energy-saving features to provide you with a low overall cost of ownership.



Specifications

Power consumption (min)

Power consumption (max)

Dimensions (W x D x H)

Net weight

mm

Weight and dimensions

Specifications	
Display/image	
Display technology	DLP
Resolution	WXGA (1280x800)
Brightness	3,700 lumens
Contrast ratio	22,000:1
Native aspect ratio	16:10
Aspect ratio - compatible	4:3,16:9
Keystone correction -	+/-40°
vertical	
Horizontal scan rate	15.38 ~ 91.15Khz
Vertical scan rate	50 ~ 85(120 for 3D)Hz
Uniformity	75%
Screen size	0.82m ~ 7.61m (32.24" ~ 299.53") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	203
Lamp life hours (up to)	6000 (Bright), 12000 (Dynamic), 10000 (Eco), 15000 (Eco+)
Optical	
Throw ratio	1.55:1 ~ 1.73:1
Projection distance (m)	1m - 12m
Zoom	1.1
Zoom type	Manual
Focal length (mm)	21.85 ~ 24
Native offset	112%
Connectivity	
Connections	Inputs 1 x HDMI 1.4a 3D support, 1 x VGA (YPbPr/RGB),
	1 x Composite video, 1 x Audio 3.5mm
	Outputs 1 x VGA, 1 x Audio 3.5mm, 1 x USB-A power 1A
	Control 1 x RS232
General	
Noise level (typical)	27dB
PC compatibility	FHD, UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
2D compatibility	NTSC M/J, 3.58MHz, 4.43MHz PAL B/D/G/H/I/M/N,
	4,43MHz SECAM B/D/G/K/K1/L, 4.25/4.4MHz 480i/p,
	576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz)
3D	3D ready
Security	Security bar, Kensington Lock, Password protected interface
OSD / display languages	25 languages: Arabic, Czech, Danish, Dutch, English, Farsi,
	Finnish, French, German, Greek, Hungarian, Indonesian,
	Italian, Japanese, Norwegian, Polish, Portuguese, Romanian,
	Russian, Chinese (simplified), Spanish, Swedish, Chinese (traditional), Turkish, Vietnamese
Operating conditions	5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m
Remote control	Card style
Speaker count	1
Speaker count Watts per speaker	1 10W
watts per speaker In the box	AC power cord
III UIE DOX	AC power cord Remote control
	Battery
	Basic user manual
Optional wireless models	HDCast Pro, QuickCast Bundle, QuickCast starter kit,
	WHD200
Power	
Power supply	100 ~ 240V, 50 ~ 60Hz
Power consumption	0.5W
(standby)	
Dower concumption (min)	1071/1

187W

225W

3kg

316 x 244 x 108



