

UHD380X

Bright 4K UHD smart home projector









- 4K UHD resolution HDR and HLG compatible
- Lights on viewing 3500 ANSI lumens
- Amazing colour accurate Rec.709 colours
- Feature packed TapCast, built-in media player and PureMotion

Immerse yourself in a world of 4K Ultra HD. The UHD380X delivers the ultimate in smart home entertainment with bright 4K UHD images, accurate colours, crystal clear detail, and sparkling contrast.

Packed with the latest technology and a range of features, this compact projector boasts High Dynamic Range (HDR) and HLG compatibility, Full 3D, HDMI 2.0, a built-in media player and PureMotion frame-interpolation processing which eliminates motion blur or image judder.

Specifications

Display/image	
Display technology	DLP
Resolution	UHD (3840x2160)
Brightness	3,500 lumens
Contrast ratio	500,000:1
Native aspect ratio	16:9
Aspect ratio - compatible	4:3
Horizontal scan rate	31 ~ 135Khz
Vertical scan rate	24 ~ 120Hz
Uniformity	75%
Screen size	0.87m ~ 7.68m (34.1" ~ 302.4") diagonal
Lamp info	
Light source type	Lamp
Lamp watts	240
Lamp life hours (up to)	4000 (Bright), 15000 (Dynamic), 10000 (Eco)
Optical	
Throw ratio	1.21:1 ~ 1.59:1
Projection distance (m)	1.2m - 8.1m
Zoom	1.3
Zoom type	Manual
Focal length (mm)	12.81 ~ 16.74
Lens shift	Vertical +10%
Native offset	105%
Connectivity	
Connections	Inputs 2 x HDMI 2.0, 1 x VGA (YPbPr/RGB), 1 x Audio
	3.5mm, 1 x USB-A reader
	Outputs 1 x Audio 3.5mm, 1 x S/PDIF, 1 x USB-A power 1.5A

General Noise level (typical) PC compatibility

UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD,

Control 1 x USB-A service, 1 x RS232, 1 x RJ45, 1 x 12V trigger, 1 x USB-A wireless, 1 x USB-A

XGA, SVGA, VGA, Mac

2D compatibility 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz),

1080p(50/60Hz), 2160p(50/60Hz)

3D compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60

Full 3D

Security Security bar, Kensington Lock, Password protected interface OSD / display languages 10 languages: English, French, German, Italian, Japanese,

Portuguese, Russian, Chinese (simplified), Spanish $5^{\circ}\text{C} \sim 40^{\circ}\text{C}$, Max. Humidity 85%, Max. Altitude 3000m

Operating conditions Backlit home remote Remote control

Speaker count 5W Watts per speaker In the box Lens cap

AC power cord Remote control 2x AAA batteries Basic user manual Wireless USB adapter - WUSB

66.00ms

Input lag Optional wireless models WUSB

Power Power supply

100 ~ 240V, 50 ~ 60Hz 0.5W

Power consumption (standby)

249W Power consumption (min) Power consumption (max) 305W

Weight and dimensions

Net weight 5.22kg Dimensions (W x D x H) 392 x 281 x 118

3D



