

UHZ65

True to life detail - Laser 4K Ultra HD projector

- Laser 4K UHD resolution and HDR compatible
- Amazing colour 80% DCI-P3, 3000 ANSI lumens
- Fluid viewing PureMotion frame interpolation
- Easy installation vertical lens shift



Designed for home cinema rooms, the UHZ65 offers unforgettable 4K digital cinema quality images in the comfort of your own home. Laser technology provides accurate, true to life colour reproduction with 80% of DCI-P3 coverage - perfect for recreating the big-screen experience at home. Packed with the latest technology and features, the stylish UHZ65 boasts High Dynamic Range (HDR) compatibility, HDCP 2.2 support and sophisticated PureMotion frame-interpolation processing which eliminates motion blurring or image judder.















Display/image

Display technology DLP

UHD (3840x2160) Resolution 3000 lumens Brightness 20000001 Contrast ratio 16:9 Native aspect ratio 4:3 Aspect ratio - compatible 31 ~ 135Khz Horizontal scan rate 24 ~ 120Hz Vertical scan rate 85% Uniformity

Lamp info

Light source Laser 20000 hours LASER life

Optical

1.39:1 - 2.22:1 Throw ratio 1.3m - 9.3m Projection distance (m) 1.6 Zoom Manual Zoom type 20.91 ~ 32.62 Focal length (mm) Vertical +15, -% Lens shift Native offset 100%

Connectivity

Inputs 1 x HDMI 2.0, 1 x HDMI 1.4a 3D support + MHL, 1 x VGA Connections

(YPbPr/RGB), 1 x Audio 3.5mm, 1 x USB-A service

 $\textbf{Outputs} \ 1 \ x \ \text{Audio} \ 3.5 \text{mm}, \ 1 \ x \ \text{S/PDIF}, \ 1 \ x \ \text{USB-A power} \ 1.5 \text{A}, \ 1 \ x \ 12 \text{V}$

trigger

Control 1 x RS232, 1 x RJ45

General

Noise level (typical) 29dB

UHD, WQHD, WUXGA, FHD, UXGA, SXGA, WXGA, HD, XGA, PC compatibility

SVGA, VGA, Mac 480i/p, 576i/p, 720p(50/60Hz), 1080i(50/60Hz), 1080p(50/60Hz), 2D compatibility

2160p(50/60Hz) Security

Security bar, Kensington Lock, Password protected interface 10 languages: English, French, German, Italian, Japanese, Portuguese, OSD / display languages

Russian, Chinese (simplified), Spanish 5°C ~ 40°C, Max. Humidity 85%, Max. Altitude 3000m

Operating conditions

Backlit home remote Remote control

2 Speaker count

4W Watts per speaker

AC power cord, remote control, 2x AA batteries, lens cap, basic user In the box

manual

Networking

Yes LAN - control

100 ~ 240V, 50 ~ 60Hz Power supply

0.5W Power consumption

(standby)

Power consumption (max) 305W

Weight and dimensions

9.5kg Net weight 498 x 331 x 141 Dimensions (W x D x H)

(mm)

Date created: 19/02/2018 17:10:28



