

EH320UST

1080p Ultra Short Throw Projector

- Bright projection 4000 ANSI lumens
- Full HD 1080p resolution, 20,000:1 contrast ratio ۲
- 2x HDMI input and 16W audio
- Crestron RoomView® RJ45 control and monitoring















EH320UST

Optoma's 1080p ultra short throw projector, the EH320UST, is perfect for businesses, schools and colleges. It is bright (4,000 lumens) and a throw ratio of 0.25:1 means that it can project a 100" image from just 55cm away. And having the projector installed so close to the screen avoids any shadows being cast across the screen from the presenter(s).

It provides a complete package for engaging learning with many new features, including two HDMI inputs, powered USB port, powerful 16W built-in speaker, improved lamp life, compact chassis and a completely new mounting system for a fast and simple set-up.

Ultra short throw



With an ultra-short throw lens, you can project an impressive image greater than 100" from just 55cm away. This allows you to place the projector closer to the wall, reducing shadows so you can present with ease; perfect for interactive applications.

Full HD 1080p

1080p resolution gives you sharp and detailed images from HD content without downscaling or compression; perfect for watching movies, viewing photos and documents.



High Contrast

Add more depth to your image with a high contrast projector; with brighter whites and ultra-rich blacks, images come alive and text appears crisp and clear - ideal for business and education applications.

Full 3D

Optoma projectors can display true 3D content from almost any 3D source, including 3D Blu-ray players, 3D broadcasting and the latest generation games consoles.



Integrated Speaker

The built-in speaker offers excellent audio support. Easy to set up without the need for costly external speakers

Eco+



Eco+ technology brings together high contrast, improved lamp life and energy saving features that are easy to use while reducing power consumption.

Energy Saving

Using the specially designed lamp modes, you can reduce the power consumption by up to 70%. Each mode also has a positive effect on the lamp life, while lowering the total cost of ownership and reducing maintenance.

Quick Resume

This feature allows the projector to be instantly powered on again, if it is accidentally switched off.

Auto power off

There may be instances when the projector is left running when not in use. To help save energy if the projector is left running and no source is detected, the "Auto power off" feature automatically turns off the projector after a set period of time.

Eco AV Mute

Stay in control of your presentation with Eco AV mute. Direct your audience's attention away from the screen by blanking the image when no longer needed. This also reduces the power consumption by up to 70%, further prolonging the life of your lamp.

Long Lamp Life

Reduce the number of lamp changes with lamp life of up to 6500 hours.

Upgrade your EPSON® UST projector to 1080p

Upgrade your EPSON® ultra short throw projector with an Optoma 1080p UST projector for higher resolution - without changing your existing mount or white board.



Remote Mouse

Keep your audience's attention focussed on the right things using the simple, yet powerful remote with USB mouse control.

Networking and Control

Featuring a wide range of options you can remotely control and monitor the projector.

- · RS232 Optoma projector's come with an extensive set of RS232 commands making it simple and easy to manage using any control system.
- AMX Compatibility Dynamic discovery protocol is incorporated into the projector allowing for easy installation with AMX control systems.
- LAN Control Using the compatible RoomView® software you can power on/off, monitor, manage and control up to 250 projectors at the same time from any computer.
 - Schedule the projectors to power on/off.
 - · Control and alter the projector settings using the simple web browser.
 - · Emergency text broadcast capabilities for urgent or important announcements.
 - · Automatically receive email updates for lamp maintenance.



Colour Guarantee

We are so confident that the image colour quality will remain as good as the day you bought it that Optoma will guarantee it for five years.



Amazing Colour

Give powerful presentations and educational lessons with stunning colours. Optoma projectors provide you with reliable colour performance suitable for any content and environment. From accurate sRGB colours for true life like images to vibrant punchy presentations. We have a display mode to specific meet your needs.





without

with

Wireless Presenting (optional extra)

Making presentations couldn't be easier using the optional wireless features of the WPS Wireless Adapter (sold separately) - you can connect and display presentations wirelessly from a laptop, PC or mobile device.



USB Power

Use the USB-Power to power an HDMI dongle, such as Google Chromecast or the Optoma WHD200 wireless HDMI device.

Specification

Resolution 1060p 1320 x 1080 f Brightness ¹ (Eight Mode) 4000 ANSI Lumens Contrast 20,000:1 Typical lamp life ² Eco+/Dynamic/Eco/Bright 6500/5000/3000 (hrs) Driver Ratio 0.25:1 Zoom Type Fixed I/O Connectors 2 x HUMI (1.4 a 3D support), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio in 3.5mm, Audio Out 3.5mm, VGA Out (Shared III) Speaker 15 * Vertical Keystone Correction 15 * Vertical Megnit (G) 478 Dimensions (W x D x H) (mm) 385 x 310 x 120 Aspect Ratio 16 9 Native, 4.3 Compatible Offset 118% Projection Distance 0.45 - 0.59m Projection Distance 0.42, H. 1.00, X5GA, VGA, NGA, NGA, NGA, NGA, NGA, NGA, NGA, N	Display Technology	Single 0.65" DarkChip 3 1080p DLP® Technology by Texas Instruments
Dimension 20,000:1 Typical lamp life ² Eco+/Dynamic/Eco/Bright 6500/5000/5000/3000 (hrs) Throw Ratio 0.25:1 Zoom Type Fixed I/O Connectors 2 x HDMI (1 4a 3D support), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (Shared with VGA2), R445, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync Speaker 16 Keystone Correction ± 5' Vertical Weight (kg) 4, 78 Dimensions (W x D x H) (mm) 385 x 310 x 120 Aspect Ratio 16.9 Natrue, 4, 32 Compatible Offset 118% Projection Distance 0,45 : 0.59m Projection Distance 0,45 : 0.59m Projection Distance 0,45 : 0.59m Viéco Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Uniformity 85% Compatibility PAL (6, D, G, H, I, M, N, 576i(p), NTSC (M, 4.43/3.58 MHz, 480/p), SECAM (8, D, G, K, K1, L) HD (1080, 720p) Yieldo Compatibility Vaca, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Uniformity Sisting-Sistic 1000:60 for 0.720p.50 / 60 Strane_Pock: 1080p24, 720p50 / 60 Orazantel, 108 - 01 HzH	Resolution	1080p 1920 x 1080
Contrast 20.000:1 Typical lamp like ² Eco+Dynamic/Eco/Bright 6500/5000/5000/3000 (hrs) Throw Ratio 0.25:1 Zoom Type Fixed I/O Connectors with VGA2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync Speaker st Keystone Correction ± 5' Vertical Weight (kg) ± 6' Vertical Offset 18% Projection Distance 0.4' 78 Offset 18% Projection Distance 0.4' 78 Offset 18% Projection Distance 0.4' 74 Offset 18% Projection Distance 0.4' 74 Offset 18% Projection Distance 0.4' 74 Outron of Stance 0.4' 74 Orapidit Compatibility 0.' CA, 1' 75/6/0, NTSC (M, 4.43/3.5' MH, 2.401/0), SECAM (B, D, C, K, K1, L) HD (1080, 720p) Video Compatibility PAL (B, D, C, H, I, M, N, 75/6/0, NTSC (M, 4.43/3.5' MH, 2.401/0), SECAM (B, D, C, K, K1, L) HD (1080, 720p) Offset 180, ''''''''''''''''''''''''''''''''''''	Brightness ¹ (Bright Mode)	4000 ANSI Lumens
Throw Ratio 0.25:1 Zoom Type Fixed I/O Connectors 2 x HDMI (1 4a 3D support), 2 x VGA (YPbP/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (Shared with VGA2), Ru45, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync Speaker 16 Keystone Correction 4 5' Vertical Wreight (kg) 4.78 Dimensions (W x D x H) (mm) 336 x 310 x 120 Aspect Ratio 16.9 Offset 118% Projection Screen Size 2.03 - 2.54m (80' - 100') Diagonal 16:9 Projection Screen Size 2.03 - 2.54m (80' - 100') Diagonal 16:9 Projection Distance 0.45 - 0.59m Projection Distance 0.45 - 0.59m Video Compatibility DKA, SKGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576/p), NTSC (M, 4.393,58 MHz, 480/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Compatibility PAL (B, D, G, H, I, M, N, 576/p), NTSC (M, 4.393,58 MHz, 480/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Compatibility PAL (B, D, C, H, I, M, N, 576/p), NTSC (M, 4.393,58 MHz, 480/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Compatibility Side-49/p, Side: 1080160 / 60, 720p50 / 60 <tr< td=""><td></td><td>20,000:1</td></tr<>		20,000:1
Throw Ratio 0.25:1 Zoom Type Fixed I/O Connectors 2:x HDMI (1 4a 30 support), 2:x VGA (YPDP/RGB), Composite, 2:x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (Shared with VGA2), Ru45, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync Speaker 16 Keystone Correction 4:5' Vertical Wreight (kg) 4:78 Dimensions (W x D x H) (mm) 336 x 310 x 120 Aspect Ratio 16:9 Native, 4:3 Compatible Offset 118% Projection Screen Size 2:03 - 2.54m (80' - 100') Diagonal 16:9 Projection Distance 0.45 - 0.59m Projection Distance 0.45 - 0.59m Ordputer Compatibility DKGA, SKGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N. 576/ip), NTSC (M, 439/35 MHz, 480/ip), SECAM (B, D, G, K, K1, L) HD (1080, 720p) 3D Support Full 80 - 10: 20 Sagnes from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility PAL (B, D, C, H, I, M, N. 576/ip), NTSC (M, 439/35 MHz, 480/ip), SECAM (B, D, G, K, K1, L) HD (1080, 720p) 3D Compatibility PAL (B, D, C, T, M, M, S76/ip), NTSC (M, 439/35 MHz, 480/ip), SECAM (B, D, C, K, K1, L) HD (1080, 720p) 3D Co	Typical lamp life ² Eco+/Dynamic/Eco/Bright	6500/5000/5000/3000 (hrs)
Zoom Type Fixed I/O Connectors 2 x HDMI (1 4a 3D support), 2 x VGA (YPDP/r/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, KGA Out (Shared with VGA2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync Speaker 16 Keystone Correction ± 5* Vertical Weight (kg) 4.78 Dimensions (W x 0 x H) (mm) 385 x 310 x 120 Aspect Ratio 16:9 Native, 4:3 Compatible Offset 118% Projection Distance 0.45 - 0.59m Projection Distance 6.45 - 0.59m Projecton Lens F/2.4; F3.72mm, Fixed Zoom Uniformity 6% Offset 20 - 7he 3D features of Optioma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modeling systems. 3D TV broadcast systems, (SKY in the UK), Bu-rag 3D** and 3D games from the Sont@ PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-108(0 / 60, 720)p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Forizontal Scan Rate 12.3 - 91.1kHz Verictial Scan Rate 12.4 - 60Hz		0.25:1
I/O Connectors 2 x HDMI (14 a 3D support), 2 x VGA (YPEP/RGB), Composite, 2 x Judio In 3.5mm, Audio Out 3.5mm, VGA Out (Shared with VGA2), RJ45, RS232, USB remote mouse/service, 12V trigger. Mic In, USB-A Power, 3D-Sync Speaker 16 Keystone Correction ± 5" Vertical Weight (kg) 4.78 Dimensions (W x D x H) (mm) 385 x 310 x 120 Aspect Ratio 16:9 Native, 4:3 Compatibile Offset 118% Projection Screen Size 2.03 - 2.54m (80" - 100") Diagonal 16:9 Projection Screen Size 2.03 - 2.54m (80" - 100") Diagonal 16:9 Projection Screen Size 2.03 - 2.54m (80" - 100") Diagonal 16:9 Projection Distance 0.45 - 0.55m Projection Lens Fi2 4; F3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (8, D, G, H, I, M, N 576/Ip), NTSC (M, 4.437,358 MHz, 480/Ip), SECAM (8, D, G, K, K1, L) HD (10801, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatibile 3D content. Typical applications include use with 3D educational or 3D design and modeling systems. 3D TV broadcast systems, S(KY in the UK), BU-ray 3D ^{**} and 3D design and modeling systems. 3D TV broadcast systems, S(SY in the UK), BU-ray 3D ^{**} and 3D design and modeling systems. 3D TV broadcast systems, S(SY in t		
Keystone Correction ± 5° Vertical Weight (kg) 4,78 Dimensions (W x D x H) (mm) 385 x 310 x 120 Aspect Ratio 16:9 Native, 4:3 Compatible Offset 118% Projection Distance 0.45 · 0.59m Projection Lens F/2.4; F3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576//p), NTSC (M, 4:33.58 MHz, 480//p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 30 - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D ^m and 3D games from the Sony® PS3 or Microsof® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side: 108050 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Power Colsumption 310W Bright mode / 260W Eco mode (< 0.5W Standby)	I/O Connectors	with VGA2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync
Weight (kg) 4.78 Dimensions (W x D x H) (mm) 385 x 310 x 120 Aspect Ratio 16:9 Native, 4:3 Compatible Offset 118% Projection Screen Size 2.03 - 2.54m (80" - 100") Diagonal 16:9 Projection Icans 6:45 - 0.59m Projection Lens Fi/2,4 (F3.72mm, Fixed Zoom Uniformity 85% Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Fuil 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modeling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D ^m and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side: 108050 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Cover-Under: 1080p24, 720p50 / 60 Over-Under: 107 Billion Noise Level (Eco mode) 28dB Power Supply 100-240V, 50-60Hz Po		1.
Dimensions (W x D x H) (mm) 385 x 310 x 120 Aspect Ratio 16:9 Native, 4:3 Compatible Offset Offset 118% Projection Distance 0.45 - 0.59m Projection Distance 0.45 - 0.59m Projection Distance 0.45 - 0.59m Optimity UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Uniformity UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Secondation Secondation 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D ^W and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080160 / 60, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 12.3 - 91.1kHz Vertical Scan Rate 24.86Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 28dB Power Supply 100-240V, 50-60Hz Power Supply 100-240V, 50-60Hz Power Con		
Aspect Ratio 16:9 Native, 4:3 Compatible Offset 118% Projection Screen Size 2.03 - 2.54m (80" - 100") Diagonal 16:9 Projection Distance 0.45 - 0.59m Projection Lens F1/2,4; [F3.72mm, Fixed Zoom Uniformity 85% Compatibility VXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p). SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broackast systems, (SKY in the UK), Blu-ray 3D TM and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080150 / 60, 720p50 / 60 Vertical Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 16.73.1kHz (120Hz for 3D) Displayable Colours 1.07 Billion Nolse Level (Eco mode) 28dB Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby)		
Offset 118% Projection Screen Size 2.03 - 2.54m (80" - 100") Diagonal 16:9 Projection Distance 0.45 - 0.59m Projection Distance 0.45 - 0.59m Projection Distance F/2.4; F3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D TM and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080160 / 60, 720p50 / 60 Vert-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Verter-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Displayable Colours 1.07 Billion Noise Level (Eco mode) 28dB Power Supply 100-240V, 50-60Hz Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby)		
Projection Screen Size 2.03 - 2.54m (80" - 100") Diagonal 16:9 Projection Distance 0.45 - 0.59m Projection Lens F1/2.4; F4.3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV brac/acst systems, (SKY in the UK), Blu-ray 3D [™] and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i60 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Vertical Scan Rate 1.5.3 • 91.1KHz Vertical Scan Rate 1.07 Billion Noise Level (Eco mode) 28dB Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby)		
Projection Distance 0.45 - 0.59m Projection Lens F/2.4, f=3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D [™] and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side: 1080150 / 60, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1 KHz Vertical Scan Rate 10.7 Billion Noise Level (Ecor mode) 28dB Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby)		
Projection Lens F/2.4; f=3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 10.7 Billion Noise Level (Eco mode) 28dB Power Supply 100-240V, 50-60Hz Power Supply 100-240V, 50-60Hz Power Supply 100-240V, 50-60Hz Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby)		
Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576/p), NTSC (M, 4.43/3.58 MHz, 480/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D [™] and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-typ-Side: 1080150 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Vertual Scan Rate 15.3 - 91.1kHz Vertical Scan Rate Vertical Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 10.7 Billion Noise Level (Eco mode) 28dB Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby)		
Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, Sröflp), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Vertical Scan Rate 15.3 - 91.1KHz Vertical Scan Rate 10.7 Billion Noise Level (Eco mode) 28dB Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby)		
Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080160 / 60, 720p50 / 60 Frame-pack: 108024, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Diver-Under: 1080p24, 720p50 / 60		++/+
3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720550 / 60 Vertical Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 14.3 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 28dB Power Supply 100-240V, 50-60Hz Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby)		
use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 28dB Power Supply 100-240V, 50-60Hz Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby)		PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p)
Frame'pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 28dB Power Supply 100-240V, 50-60Hz Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby)	3D Support	use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification.
Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 28dB Power Supply 100-240V, 50-60Hz Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby)		Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60
Displayable Colours 1.07 Billion Noise Level (Eco mode) 28dB Power Supply 100-240V, 50-60Hz Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby)		15.3 - 91.1kHz
Noise Level (Eco mode) 28dB Power Supply 100-240V, 50-60Hz Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby)	Vertical Scan Rate	24 - 85Hz (120Hz for 3D)
Power Supply 100-240V, 50-60Hz Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby)		1.07 Billion
Power Consumption 310W Bright mode / 260W Eco mode (< 0.5W Standby)	Noise Level (Eco mode)	28dB
Lamp Type 260W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian Standard Accessories AC power cord, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, wall mount Optional Wireless Yes		
Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian Standard Accessories AC power cord, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, wall mount Optional Wireless Yes		310W Bright mode / 260W Eco mode (< 0.5W Standby)
Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian Standard Accessories AC power cord, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, wall mount Optional Wireless Yes	Lamp Type	260W
On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian Standard Accessories AC power cord, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, wall mount Optional Wireless Yes		
Russian, Finnish, Ğreek, Hungarian, Czech, Arabic, Traditional Čhinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian Standard Accessories AC power cord, remote control, battery, quick start card, CD user manual Optional Accessories DLP® Link™ 3D glasses, wireless, wall mount Optional Wireless Yes		
Optional Accessories DLP® Link™ 3D glasses, wireless, wall mount Optional Wireless Yes	On Screen Display	Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai,
Optional Wireless Yes		
RoHS Compliant		
	RoHS	Compliant



Optoma Europe Ltd. 1 Bourne End Mills, Hemel Hempstead, Hertfordshire HP1 2UJ, UK www.optoma.co.uk

¹Brightness and lifetime dependent on settings and environmental conditions

²Typical lamp life achieved through testing. Will vary according to operational use and environmental conditions

20/07/2018 07:53