

Dünyanın En Küçük ve En Hafif 30.000 lm 3 Çipli DLP™ Projektörleri

PT-RQ35K

Canlı kırmızılar ve daha doğru maviler ultra detaylı 4K veya WUXGA görüntü üretimi için gerçekçiliği artırır.



KEY FEATURES

- Lazer 3 çipli DLP, 32.000 lümen (merkez), 4K (Quad Piksel Sürücü Açık İken)
- Toza dayanıklı sıvı soğutma sistemine ve bakım gerektirmeden 20.000 saatlik çalışma süresine sahip lambasız lazer projeksiyon
- IP adresi belirleme gibi ağ yapılandırmasına mobil erişim için NFC ile Akıllı Projektör Kontrolü
- Geo Pro Yazılımı için Önceden Etkinleştirilmiş Yükseltme Kitleri
- İki mavi ve bir kırmızı lazer renk gamı üretimini genişletir

SPECIFICATIONS

Dimensions (W x H x D)	Approx. 598 x 353 x 780 mm (23 17/32" x 13 29/32" x 30 23/32") (not including protruding parts)
Power Consumption	2,550 W (Standby: 14 W)
Lens	Optional (no lens included with this model)
Resolution	4K (3840 x 2400 pixels) (Quad Pixel Drive: ON)
Operating Environment	Operating temperature: 0–45 °C (32–113 °F*7), operating humidity: 10–80 % (no condensation)
Keystone Correction Range	Vertical: ±45 ° (±40 ° with ET-D75LE10/ET-D3LEW10/ET-D75LE20/ET-D3LES20, ±28 ° with ET-D75LE6/ET-D3LEW60, ±22 ° with ET-D3LEW50, ±15 ° with ET-D3LEW200, ±8 ° with ET-D3LEU100, +5 ° with ET-D75LE95), Horizontal: ±40 ° (±15 ° with ET-D3LEW50/ET-D75LE6/ET-D3LEW60, ±5 ° with ET-D3LEU100/ET-D3LEW200, 0 ° with ET-D75LE95) When [VERTICAL KEYSTONE] and [HORIZONTAL KEYSTONE] are used simultaneously, correction cannot be made exceeding a total of 55 °.
Applicable Software	Logo Transfer Software, Multi Monitoring & Control Software, Early Warning Software, Smart Projector Control for iOS/Android™
Contrast Ratio*1	20,000:1 (Full On/Full Off, Dynamic Contrast [3])
Power Supply	AC 200 V–240 V (Light output will decrease when using the projector with AC 100 V to AC 120 V)
Light Source	Laser diodes (Blue LD, Red LD)
Terminals DVI-D In	-
Terminals Serial In	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)
Terminals LAN	RJ-45 x 1 for network connection, PJLink™ (Class 2) compatible, 10Base-T/100Base-TX, Art-Net compatible
Terminals DC Out	USB Type A x 2 (for power supply, DC 5 V total of 2 A)
DLP™ Chip Panel Size	24.4 mm (0.96 in) diagonal (16:10 aspect ratio)
DLP™ Chip Display Method	DLP™ chip x 3, DLP™ projection system
Terminals SDI In	-
Terminals HDMI In	HDMI x 1 (Deep Color, compatible with HDCP 2.2, 4K/60p signal input*5)
Terminals Serial Out	D-sub 9-pin (male) x 1 for link control (RS-232C compliant)
Terminals USB	USB connector (Type A) x 1 for optional Wireless Module (AJ-WM50 Series)/USB Memory Stick
Terminals DIGITAL LINK	RJ-45 x 1 for network and DIGITAL LINK connection (HDBaseT™ compliant), 100Base-TX, compatible with Art-Net, PJLink™ (Class 2), Deep Color, HDCP 2.2, 4K/60p signal input*5
Terminals Remote 2 In	D-sub 9-pin (female) x 1 for external control (parallel)
Terminals Expansion Slot	SLOT 1/SLOT 2 (total two terminals, vacant) for interface boards, SLOT NX compatible
Terminals Multi Projector Sync In	BNC x 1
Terminals Multi Projector Sync Out	BNC x 1
Light output	30,500 lm*1/32,000 lm (Center)*2
Terminals REMOTE 1 IN	M3 stereo mini-jack x 1 for wired remote control
Terminals REMOTE 1 OUT	M3 stereo mini-jack x 1 for link control
Operation noise*1	49 dB (Normal), 46 dB (Quiet)
Projector type	3-Chip DLP™ projector
DLP™ chip Number of Pixels	2,304,000 (1920 x 1200 pixels) x 3
Screen size [diagonal]	1.78–25.4 m (70–1,000 in), 1.78–15.24 m (70–600 in) with ET-D75LE8/ET-D3LET80, 3.05–15.24 m (120–600 in) with ET-D75LE95
Center-to-corner zone ratio*1	90 %
Time until light output declines to 50 %*3	20,000 hours (Normal), 24,000 hours (Eco), 26,000 hours (Quiet)

Lens shift*4 Vertical(From the origin point of the lens mounter)	±55 % (+78 %, +68 % with ET-D75LE95, ±48 % with ET-D3LEW200, ±44 % with ET-D75LE6/ET-D3LEW60) (powered)
Lens shift*4 Horizontal(From the origin point of the lens mounter)	±20 % (±15 % with ET-D75LE6/ET-D3LEW60/ET-D3LEW200, ±12 % with ET-D75LE95, +25 %, 0 % with ET-D3LEU100) (powered)
Terminals Multi Projector Sync In/3D Sync IN/OUT	-
Terminals Multi Projector Sync Out/3D Sync Out	-
Note	*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2020 international standards. Value is average of all products when shipped. *2 Average light-output value of all shipped products measured at center of screen in NORMAL Mode. *3 Around this time, light output will have decreased by approximately 50 %. IEC62087: 2008 Broadcast contents, Normal Mode, Dynamic Contrast [3], under conditions with 35 °C (95 °F), 700 m (2,297 ft) above sea level, and 0.15 mg/m ³ of particulate matter. Estimated time until light output decreases to 50 % will vary depending on environment. *4 Lens shift is not supported on the ET-D3LEW50. *5 4K signals are converted to WUXGA (1920 x 1200 pixels) only for the PT-RZ34K. *6 Average value. May differ depending on the actual unit. *7 When optional AJ-WM50 wireless module is attached, operating temperature range becomes 0–40 °C (32–104 °F). The operating environment temperature should be between 0 °C (32 °F) and 40 °C (104 °F) if the projector is used at an altitude between 1,400 m (4,593 ft) and 4,200 m (13,780 ft).
Weight*6	69.8 kg (153.9 lbs)

URL: <https://business.panasonic.com.tr/visual-system/pt-rq35k-0>

CONTACT

Web: <https://business.panasonic.com.tr/visual-system/contact-us>